



NOTE
J4 ISOLATED FROM CHASSIS

* 6RS20SP7B7
OR
1RCKZ70PM
** 6RS20SP20B20
OR
1RCKZ200PM

4. ADJUST R8A TO ALLOW 6V DC DROP ACROSS R30(1K) SCREEN RESISTOR.

NOTE:
1 ALL CAPACITANCE VALUES ARE IN MFD UNLESS OTHERWISE SPECIFIED.
2 ALL RESISTANCE VALUES ARE IN Ω AT 1% UNLESS OTHERWISE SPECIFIED.
3 TWO IN506 CONTROLLED AVALANCHE TYPE RECTIFIERS IN EACH LEG MAY BE SUBSTITUTED FOR THE 3 PH204 IN EACH LEG.



REVISION NO.	DATE	BY
10	NOV 20, 70	AK
11	DEC 2/70	AK
12	DEC 2/70	AK
13	DEC 9/70	AK
14	JULY 18, 71	S. J.
15	JULY 18, 71	S. J.
16	AUG 5, 71	S. J.
17	FEB 17, 72	S. J.
18	MAY 17, 72	S. J.
19	OCT 5/72	SMR/KS/AK

YORKVILLE SOUND LTD.	
TELETYPE UNIT OTHERWISE SPECIFIED	DECIMAL FRACTIONAL ANGULAR
DESIGN: P. TRAYNOR	DATE: JAN 13/67
SCALE:	APPROVED:
CUSTOM SPECIAL	
ALL DIMENSIONS IN INCHES 80 NOT SCALE	

LAST CAPACITOR C35 LAST RESISTOR NO 52